

Outback[®] Rider

4WD Ride-On Brush Cutter



Lawn Care & Maintenance Machinery

Clean Up Your
World[™]



Cutting & Mowing - Outback® Rider Series



Outback® Rider 92 cm



Outback® Rider 132 cm

Outback® Rider

92 cm / 110 cm / 132 cm

Billy Goat Outback® brush cutters have set the highest standard for commercial brush-cutting equipment on the market. The Outback® Rider offers unique features and benefits to combat the most demanding conditions. When rough and overgrown areas limit the use of conventional mowers, this robust machine delivers the ultimate performance needed.

The Outback® Rider has been designed with a low center of gravity in combination with a four-wheel drive system that enables it to tackle those hard-to-reach places that wouldn't have been accessible to traditional machines. The spacious platform provides sufficient space and comfort for the operator.

The heavy-duty 92 cm mower deck is equipped with swing-back cutter blades that swing away when contact is made with a solid object. These features help to protect the mower deck and cutter blades from accidental damage. Because of the high blade speed, this deck is ideal for mowing thick brush.

The 110 and 132 cm fabricated mower decks with open front design have three spindles hosting crossed mulching blades that are also offset vertically. This enhances their mulching performance in high grass conditions with excellent particle reduction.

Look no further than the Billy Goat Outback® Rider when you are looking for the ultimate brush cutting machine.




Vanguard™ EFI (Electronic Fuel Injection) provides a wide range of benefits for a versatile line of applications. These benefits include reduced fuel consumption providing up to 25% better fuel economy than a carbureted engine* (closed-loop systems only), increased power, improved resistance to stale fuel (due to ethanol blends), and engine performance that increases governing control and load acceptance. Vanguard™ EFI systems also deliver optimized starting, including cold & hot restart and chokeless starting.

* Fuel savings may vary based on cutting conditions and other factors.



Features



Professional Engine

The 28 HP Vanguard™ 810cc EFI engine features reduced fuel consumption, increased governing control and load acceptance, optimized chokeless starting and altitude compensation - all ideal for commercial turf applications.



ROPS Structure

A certified ROPS (Roll Over Protection Structure) with safety belt protects the machine and operator from rolling over and can fold 180 degrees backwards to allow for easier loading inside a van or trailer.



User Friendly Dashboard

The operator's compartment features a dashboard with control and warning lights, electric PTO engagement switch with soft start function, steering wheel with tilt-function and spinner knob, cruise control switch and a parking-brake lever.



Heavy-Duty Bumpers

The wide front and rear bumpers protect the rider against accidental impacts and incorporate tie-down points for securing the machine during transportation.




Durable Mower Deck

The 92 cm fabricated deck has been designed for heavy-duty brush cutting and discharges clippings rearwards. Replaceable swing-back cutter blades reduce accidental blade damage, with flip-up lids on the side of the deck providing easy access to the swing-back cutters when needed.



Ergonomic Operator's Platform

The large operator's platform provides sufficient space for even the tallest user. Secondary footrests provide a secure foothold especially for use on hillsides. The contoured seat with armrests keeps you comfortable all day and is equipped with fore and aft positioning. Integrated handrails provide a secure grip on the machine when needed.



Drive System

The Tuff Torq™ 4WD system automatically controls the output to all drive wheels. Combined with a manual locking differential, this 4WD system provides all the traction you need in challenging terrain.



Clean Air

The large Donaldson® dual-stage industrial cyclonic air cleaner keeps the incoming air clean and extends the service interval by 4x when compared to a traditional panel-style air filter.



Drive Wheels

Large drive wheels with agricultural tread ensure sufficient grip. The pivoting front axle allows all four driven wheels to remain in contact with the ground for maximum traction.



Transmission Oil Cooler

A remote transmission oil cooler controls the transmission oil temperature even in the toughest conditions, reducing thermal oil breakdown and extending the operating life of the system.



Outback® Rider 92 cm

Specifications Outback® Rider

USE / LEVEL		FOR COMMERCIAL USE / ROUGH TERRAIN, HILLSIDES & HIGH VEGETATION		
Model	Outback® Rider 92 cm		Outback® Rider 110 cm	Outback® Rider 132 cm
Model number	2691744		2691819	2692086 (power unit) + 1697617 (deck)
ENGINE				
Engine brand / model	Vanguard™ 810cc EFI, V-Twin			
Engine performance	28 gross HP*			
Air filtration	Donaldson® 2-stage cyclonic air cleaner			
Fuel	Petrol (up to 10% ethanol)			
Fuel tank capacity (liter)	16			
BRUSH CUTTER				
Cutting width (cm / inch)	92 / 36"		110 / 43"	132 / 52"
Height-of-cut (cm)	5 - 13,5 cm (in transport mode max. 16 cm)		4 - 12,5 cm (in transport mode max. 16 cm)	4 - 12,5 cm (in transport mode max. 16 cm)
Height-of-cut positions	5 + 1 transport position			
Blades	1, with swing-back cutter blades		3, cross blades	3, cross blades
Anti-scalp wheels	-		2	2
Drive system	Tuff Torq 4WD system with K664 hydrostatic transaxle and KXH-10 front axle			
Transmission cooling	Remote oil cooler with electric fan			
Parking brake	Internal transaxle			
PTO clutch	Warner electromagnetic clutch			
Deck drive system	B-section belt with soft start function			
Forward speed (km/h)	0 - 9,5			
Reverse speed (km/h)	0 - 7,5			
Differential lock	Standard, lever activated			
Front wheel (inch)	16 x 6,50 - 8, agricultural tread			
Rear wheel (inch)	20 x 10,00 - 8, agricultural tread			
Steering method	Mechanical Steering			
Seat	Adjustable contoured seat with armrests and seat belt			
Lights	Halogen front lights and LED contour light front and rear			
Display control lights	Mower deck engagement, parking brake, oil pressure, battery, fuel level warning, cruise control, hour meter			
Bumper	Front and rear			
OTHER INFORMATION				
Length x Width x Height (mm)	2350 x 1040 x 1740		2350 x 1160 x 1740	2350 x 1360 x 1740
Wheel base (mm)	1485			
Minimum turning radius (mm)	1280			
Rear wheel internal radius (mm)	750			
Weight (kg)	403		412	427
Maximum inclination (°)	22			

* All power levels are stated gross HP at 3,600 RPM per SAE J1940 as provided by Briggs & Stratton.

Distributed by

Henton & Chattell Ltd
London Road
Nottingham
NG2 3HW
United Kingdom
www.billygoat.co.uk

Your Billy Goat Dealer

WWW.BILLYGOAT.EU

BRIGGS & STRATTON NETHERLANDS BV • SCHEPERSWEG 4C, 6049 CV HERTEN • THE NETHERLANDS • Tel: +31 (0)475 408 383

Copyright ©2025 All rights reserved. 01/2025 EN-BCR
Briggs & Stratton has a policy of continuous product improvement and reserves the right to modify its specifications at any time and without prior notice. Products may vary from images shown.
No liability can be accepted for printing errors.